

Ref. **9BONI10**

Indoor and dry environments

Low

Low shoes



The +

EN ISO 20347 Personal protective equipment - Occupational footwear.

*Open shoe to be protected without suffering from heat.

*Defined heel for better safety especially on ladders.

PURCHASE PACKAGING

Ref.	Size	Carton
9BONI10035	35	10
9BONI10036	36	10
9BONI10037	37	10
9BONI10038	38	10
9BONI10039	39	10
9BONI10040	40	10
9BONI10041	41	10
9BONI10042	42	10
9BONI10043	43	10
9BONI10044	44	10
9BONI10045	45	10
9BONI10046	46	10
9BONI10047	47	10
9BONI10048	48	10

Some sizes may only be available in certain countries



DESCRIPTION

- * Protecting sandals with soft, well ventilating nubuck leather uppers
- * Antistatic, oil- and acid-proof, flexible double-layer PU soles
- * SRC anti-slip protection tested on wet ceramic surfaces

SECTORS

Light Industries

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

Color	Black	Lining	Breathable 3D mesh
Weight	548 g		
Upper	Nubuck leather		
Midsole	PU		
Outsole	PU		
Insole	Removable, perforated EVA		
Main assembly	Injected		
Closing	Scratch closure		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/08/24/1838

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance

EN ISO 20347:2022

Work shoes

O1

Basic requirements - construction and safety + closed heel area + E + A