

Ref. **9BONO10**

Indoor and dry environments

Low

Sandals



S1



The +

*Open shoe to be protected without suffering from heat.

*Defined heel for better safety especially on ladders.

PURCHASE PACKAGING

| Ref. | Size | Carton |
|------------|------|--------|
| 9BONO10035 | 35 | 10 |
| 9BONO10036 | 36 | 10 |
| 9BONO10037 | 37 | 10 |
| 9BONO10038 | 38 | 10 |
| 9BONO10039 | 39 | 10 |
| 9BONO10040 | 40 | 10 |
| 9BONO10041 | 41 | 10 |
| 9BONO10042 | 42 | 10 |
| 9BONO10043 | 43 | 10 |
| 9BONO10044 | 44 | 10 |
| 9BONO10045 | 45 | 10 |
| 9BONO10046 | 46 | 10 |
| 9BONO10047 | 47 | 10 |
| 9BONO10048 | 48 | 10 |

Some sizes may only be available in certain countries

DESCRIPTION

BONO shoe is a shoe with a nubuck leather upper, reflective trim on both sides and moisture wicking non-woven lining. This open shoe permits to be protected without suffering from heat. This model is equipped of a steel toe cap a for a better protection against perforation and falling of heavy objects. It has a fuel and oil resistant contact outsole on ceramic or steel floor.

SECTORS

Light Industries

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

| | | | |
|---------------|---------------------------|---------|--------------------|
| Color | Black | Closing | Scratch closure |
| Weight | 545 g | Lining | Breathable 3D mesh |
| Upper | Nubuck leather | | |
| Toecap | Steel | | |
| Midsole | PU | | |
| Outsole | PU | | |
| Insole | Removable, perforated EVA | | |
| Main assembly | Injected | | |

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate LECFI00381071

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S1

Safety shoes

S1 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol