

Ref. **9BLAC10**

Outdoor

High

High shoes



The +

- * PU/PU "soft" outsole: cushioning
- * Defined heel: stability on ladder.
- * Large side zip: easy to put on.
- * Foam insole with cushioning : comfort

PURCHASE PACKAGING

Ref.	Size	Carton
9BLAC10036	36	4
9BLAC10037	37	4
9BLAC10038	38	4
9BLAC10039	39	4
9BLAC10040	40	4
9BLAC10041	41	4
9BLAC10042	42	4
9BLAC10043	43	4
9BLAC10044	44	4
9BLAC10045	45	4
9BLAC10046	46	4
9BLAC10047	47	4
9BLAC10048	48	4
9BLAC10049	49	4

Some sizes may only be available in certain countries



DESCRIPTION

BLACK STAR is a safety ranger, with a grained leather and Oxford fabric upper.

Its outsole is made of low density PU/PU, which makes the model comfortable.

BLACK STAR is equipped with a composite toe cap and a textile puncture resistant sole, for lightness and flexibility.

A large side zipper makes it easy to put on and take off.

SECTORS

Extracting Oil and Gas

Manufacture of electrical and electronic equipment and machines

Regional/public authorities

Infrastructure, building industry

APPLICATIONS

Builder,
Slater,
Ramp agent,
Luggage handler,
Site supervisor,
Dockers, ...

TECHNICAL FEATURES

Color	Black	Closing	Lacing closure
Upper	Oxford / Grained leather	Lining	Breathable 3D mesh
Toecap	Composite	Weight	695 g
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		
Main assembly	Injected		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/12/21/2226

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

COVERPERF - Damping



EN ISO 20345:2022

S3S

Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

Safety shoes

S3S Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton+ closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value ≥ 950 N) - Non-metallic insert, 3.0mm diameter puncture needle+ non-metallic insert type PS - resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance