

Ref. **9FREL**

Multipurpose

High

High shoes



S3



0%
METAL

The +

- * Footbridge supplying torsional rigidity.
- * Padding for snug fit.

PURCHASE PACKAGING

Ref.	Size	Carton
9FREL36	36	10
9FREL37	37	10
9FREL38	38	10
9FREL39	39	10
9FREL40	40	10
9FREL41	41	10
9FREL42	42	10
9FREL43	43	10
9FREL44	44	10
9FREL45	45	10
9FREL46	46	10
9FREL47	47	10
9FREL48	48	10

Some sizes may only be available in certain countries

See also

DESCRIPTION

Upper in granulated leather, water repellent
 Padded collar for more protection and more comfort
 External sole in PU double density
 Antipenetration textile sole, nonmagnetic
 Composite toecap, nonmagnetic
 Breathable textile lining

SECTORS

Infrastructure, building industry
 Construction - finishing work
 Transport (excluding manufacturing) and logistics
 Services and distribution

APPLICATIONS

Luggage handler,
 Delivery driver, ...

VARIANTS



9FREL

TECHNICAL FEATURES

Color	Black	Closing	Lacing closure
Upper	Full grain leather	Lining	Breathable 3D mesh
Toecap	Composite	Weight	602 g
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		
Main assembly	Injected		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC FI00379241**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

SRC

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol