coverguard

TECHNICAL DATASHEET


GALENA

Ref. 9GAL140

Indoor and dry environments

Low





The +

*Trendy design. *Breathability. *PU2D injected sole. *Reflective stripes (9GAL500).

PURCHASE PACKAGING

Ref.	Size	Carton
9GAL140038	38	10
9GAL140039	39	10
9GAL140040	40	10
9GAL140041	41	10
9GAL140042	42	10
9GAL140043	43	10
9GAL140044	44	10
9GAL140045	45	10
9GAL140046	46	10
9GAL140047	47	10

Some sizes may only be available in certain countries

VARIANTS

See also



9GAL500

DESCRIPTION

GALENA is a low safety shoe inspired by sport.

It features an upper made of perforated suede leather and a lining in Polyester mesh which provide high breathability.

The outsole resists to fuel and oil contact.

It is slip resistant on ceramic or steel floor and offer protection and stability to the wearer.

Its PU/PU double density construction provides comfort and durability. The insole made of textile fabric and EVA with holes guarantees an efficient cushioning and breathability.

This model is equipped with a steel toe-cap and anti-penetration plate. This shoe is ideal for working environments such as logistics, light industry or maintenance.

Painter,

Electrician,

Storekeeper, ...

APPLICATIONS

SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

coverguard

GALENA

TECHNICAL FEATURES

Color	Beige
Color 2	Yellow
Weight	590 g
Upper	Suede leather
Тоесар	Steel
Puncture resistant	Steel
sole	
Midsole	PU
Outsole	PU

Insole Main assembly Closing Lining Removable, perforated EVA Injected Lacing closure Breathable 3D mesh

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/07/19/2029

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France

CE	EPI CAT. II	
EN ISO 20345:2011	Safety shoes	
S1P	S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure	
252		

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol