

Ref. **9HILL**

Indoor and dry environments

Low

Low shoes

S1P



HRO

0%
METAL



The +

- * Breathable upper and lining.
- * Padded collar and bellows tongue for snug fit.

PURCHASE PACKAGING

Ref.	Size	Carton
9HILL39	39	10
9HILL40	40	10
9HILL41	41	10
9HILL42	42	10
9HILL43	43	10
9HILL44	44	10
9HILL45	45	10
9HILL46	46	10

Some sizes may only be available in certain countries

See also

VARIANTS



9HILH

DESCRIPTION

Composite toecap
 Antipenetration textile Wellmax sole
 External sole in Rubber
 Reinforcement : front in Nubuck
 Textile tightening loops, High shoes plastic hooks
 Padded collar
 Upper in Nubuck
 Breathable mesh lining
 Padded tongue

SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Painter,
 Electrician,
 Storekeeper, ...

TECHNICAL FEATURES

Color	Black	Main assembly	Cemented
Color 2	Grey	Closing	Lacing closure
Weight	612 g	Lining	Breathable 3D mesh
Upper	Polyamide mesh / Nubuck leather		
Toecap	Composite		
Puncture resistant sole	Textile		
Outsole	Rubber nitrile		
Insole	Removable, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100330566**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)