

HILLITE

Ref. **9HILL**

Indoor and dry environments

Low

Low shoes

S1P



0%
METAL



The +

- * Breathable upper and lining.
- * Padded collar and bellows tongue for snug fit.

PURCHASE PACKAGING

| Ref. | Size | Carton |
|------|------|--------|
|------|------|--------|

Some sizes may only be available in certain countries

See also

VARIANTS



9HILH

DESCRIPTION

Composite toecap
 Antipenetration textile Wellmax sole
 External sole in Rubber
 Reinforcement : front in Nubuck
 Textile tightening loops, High shoes plastic hooks
 Padded collar
 Upper in Nubuck
 Breathable mesh lining
 Padded tongue

SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Painter,
 Electrician,
 Storekeeper, ...

TECHNICAL FEATURES

| | | | |
|-------------------------|---------------------------------|---------------|--------------------|
| Color | Black | Main assembly | Cemented |
| Color 2 | Grey | Closing | Lacing closure |
| Weight | 612 g | Lining | Breathable 3D mesh |
| Upper | Polyamide mesh / Nubuck leather | | |
| Toecap | Composite | | |
| Puncture resistant sole | Textile | | |
| Outsole | Rubber nitrile | | |
| Insole | Removable, textile and foam | | |

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100373251**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)