

Ref. **9CHSA**

Synthetic Boots

PVC

Waders



S5



The +

* Waterproof protection while working in the water.

PURCHASE PACKAGING

Ref.	Size	Carton
9CHSA39	39	3
9CHSA40	40	3
9CHSA41	41	3
9CHSA42	42	3
9CHSA43	43	3
9CHSA44	44	3
9CHSA45	45	3
9CHSA46	46	3
9CHSA47	47	3

Some sizes may only be available in certain countries

DESCRIPTION

Steel toecap
 Steel antipenetration sole
 External sole in black PVC
 Upper in green PVC
 White polyester lining
 Crotch height: 50 cm

SECTORS

Heavy & process industries

Light Industries

Food-processing industry

Regional/public authorities

TECHNICAL FEATURES

Color	Green
Color 2	Black
Weight	1 505 g
Upper	PVC
Toecap	Steel
Puncture resistant sole	Steel
Outsole	PVC nitrile
Lining	Polyester

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These Chest Waders can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the Chest Waders, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the Chest Waders by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate CE-2790-105/2022

Delivered by ASSOCIAÇÃO PORTUGUESA DOS INDUSTRIAIS DO CALÇADO - COMPONENTES-ARTIGOS DE PELE E SEUS SUCEDÂNEOS (APPICAPS) (2790) RUA ALVES REDOL - 372 4050-040 PORTO - Portugal



EPI CAT. II

EN ISO 20345:2011

S5

Safety shoes

S5 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol