

Ref. **9DEVO40**

Synthetic Boots

PVC

Boots



S5



The +

- * Excellent grip thanks to an oil resistant outsole.
- * Waterproof.
- * Energy absorption in the heel area.

PURCHASE PACKAGING

Ref.	Size	Carton
9DEVO40036	36	8
9DEVO40037	37	8
9DEVO40038	38	8
9DEVO40039	39	8
9DEVO40040	40	8
9DEVO40041	41	8
9DEVO40042	42	8
9DEVO40043	43	8
9DEVO40044	44	8
9DEVO40045	45	8
9DEVO40046	46	8
9DEVO40047	47	8

Some sizes may only be available in certain countries

DESCRIPTION

Steel toecap
 Steel antipenetration sole
 External sole in white PVC
 White PVC upper
 White polyester lining

SECTORS

Food-processing industry

TECHNICAL FEATURES

Color	White
Weight	944 g
Upper	PVC
Toecap	Steel
Puncture resistant sole	Steel
Outsole	PVC nitrile
Lining	Polyester

INSTRUCTION FOR USE AND STORAGE

Instructions for use

Storage instructions

Washing instructions

STANDARD(S)



EN ISO 20345:2011

S5

SRA

Safety shoes

S5 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol