

Ref. 1NIBG

Handling and Precision Works

Oily Environment



The +

3/4 coating: increased skin protection against dermatitis risks
Ergonomical shape
Excellent comfort
Second skin sensation
Exceptional grip in oily areas

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1NIBG06	6	10	100
1NIBG07	7	10	100
1NIBG08	8	10	100
1NIBG09	9	10	100
1NIBG10	10	10	100
1NIBG11	11	10	100

SALES PACKAGING

Hangable individual polybag

See also

VARIANTS



1N1SG

DESCRIPTION

Grey seamless support from polyamide, 15 gauge,
Double coating, 3/4 smooth black nitrile with sandy palm finish,
Ergonomic shape,
Knitted wrist
Certified OEKO-TEX® STANDARD 100, CQ 1301/1, IFTH or 15.HCN.70502, HOHENSTEIN

SECTORS

- Heavy & process industries
- Light Industries
- Maintenance
- Services and distribution

APPLICATIONS

Suitable for all fine work in oily and greasy environments, mechanical and automotive industries, machining of parts in the presence of cutting oil, handling of sheet metal, oiled mechanical parts and sorting of small parts, maintenance work in wet environments, water, oils, greases, hydrocarbons, assembly of small oily parts, small general maintenance and maintenance work.

TECHNICAL FEATURES



Gauge 15

Color	Grey	Type Of Cuff	Elastic wrist
Color 2	Black		
Shape	Glove		
Gloves environment	Oily		
Glove type	Seamless knitting		
Support material	Polyamide, elastane		
Coating level	3/4		
Material of coating	Nitrile		
Coating finition	Smooth		
Coating level	Palm		
Material of coating	Nitrile		
Coating finition 2	Sandy		

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/162/01/23/0045

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN388:2016
+ A1:2018

Protection from mechanical risks



4.1.3.1.X.