

Ref. **9DUAC80**

Synthetic Boots

PU

Boots



S5



MADE IN EUROPE

The +

- * Flexible and lightweight for use all day long.
- * Shaped cleats and raised heel for a perfect gripping
- * Cold insulation.
- * Antibacterial lining
- * Scented comfort insole

PURCHASE PACKAGING

Ref.	Size	Carton
9DUAC80036	36	5
9DUAC80037	37	5
9DUAC80038	38	5
9DUAC80039	39	5
9DUAC80040	40	5
9DUAC80041	41	5
9DUAC80042	42	5
9DUAC80043	43	5
9DUAC80044	44	5
9DUAC80045	45	5
9DUAC80046	46	5
9DUAC80047	47	5
9DUAC80048	48	5

Some sizes may only be available in certain countries

DESCRIPTION

The DRY'PU ACTIVE model is a Polyurethane (PU) safety boot lined with an antibacterial lining.

This boot features a protective toe cap and steel midsole against impact and penetration.

Its PU outsole is reinforced with a TPU insert and insulates against the cold down to -20 ° C.

SECTORS

Farming, silviculture and fishing

Energy (production and distribution)

Regional/public authorities

Infrastructure, building industry

TECHNICAL FEATURES

Color	Green	Insole	Foam, removable and scented
Color 2	Black	Defined heel	
Weight	1109 gr		
Upper	Polyurethane		
Toecap	Steel		
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate CE 75776

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9- 1066 EP Amsterdam Netherlands



EPI CAT. II

EN ISO 20345:2011

S5

Safety shoes

S5 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

CI

Shoe insulation against cold (30 minutes at -20°C)