

Ref. **9FREL**

Multipurpose

Low

Low shoes



The +

- * Footbridge supplying torsional rigidity.
- * Padding for snug fit.

PURCHASE PACKAGING

Ref.	Size	Carton
9FREL36	36	10
9FREL37	37	10
9FREL38	38	10
9FREL39	39	10
9FREL40	40	10
9FREL41	41	10
9FREL42	42	10
9FREL43	43	10
9FREL44	44	10
9FREL45	45	10
9FREL46	46	10
9FREL47	47	10
9FREL48	48	10

Some sizes may only be available in certain countries

See also

DESCRIPTION

Upper in granulated leather, water repellent
 External sole in PU double density
 Antipenetration textile sole, nonmagnetic
 Composite toecap, nonmagnetic
 Breathable textile lining

SECTORS

- Infrastructure, building industry
- Construction - finishing work
- Transport (excluding manufacturing) and logistics
- Services and distribution

APPLICATIONS

Luggage handler,
 Delivery driver, ...

VARIANTS



9FREH

TECHNICAL FEATURES

Color	Black	Main assembly	Injected
Weight	563 g	Closing	Lacing closure
Upper	Full grain leather	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/06/24/1221 Ext 01/06/24

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S3S

Safety shoes

S3S Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton+ closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value \geq 950 N) - Non-metallic insert, 3.0mm diameter puncture needle+ non-metallic insert type PS - resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance