

Ref. **9DWKT10**

Synthetic Boots

PVC

Boots



The +

- *Excellent grip thanks to an oil-resistant sole.
- *Highest SR class anti-slip power, for perfect grip on all terrains. *Energy absorption in the heel area.
- *Improved fit and support

PURCHASE PACKAGING

Ref.	Size	Carton
9DWKT10036	36	6
9DWKT10037	37	6
9DWKT10038	38	6
9DWKT10039	39	6
9DWKT10040	40	6
9DWKT10041	41	6
9DWKT10042	42	6
9DWKT10043	43	6
9DWKT10044	44	6
9DWKT10045	45	6
9DWKT10046	46	6
9DWKT10047	47	5

Some sizes may only be available in certain countries

DESCRIPTION

The Work-it boot is a waterproof safety boot made from recycled PVC and lined with polyester. Non-slip on ceramic floors, its PVC sole is also antistatic and resistant to hydrocarbons. This work boot is equipped with a protective shell as well as a steel midsole against shocks and penetration.

SECTORS

Farming, silviculture and fishing

Light Industries

Regional/public authorities

Infrastructure, building industry

DIY

TECHNICAL FEATURES

Color	Black
Color 2	Black
Weight	1096g
Upper	PVC
Toecap	Steel
Puncture resistant sole	Steel
Outsole	PVC nitrile
Lining	Polyester

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate CE-1775-42R/12

Delivered by CTCP (1775) Rua de Fundões- Devesa Velha 3700 - 121 S. João da Madeira Portugal



EPI CAT. II

EN ISO 20345:2022

S5

SR

LG

Safety shoes

S5 Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton and:- closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Sole puncture resistance (1100 Newton)- Metallic insert, 4.5mm diameter puncture needle- cleated outsole

Resistance to slippage (ceramic floor + oil)

Grip System - Unhooked heel