

Ref. **9DWKT80**

Synthetic Boots

PVC

Boots



S5



MADE IN EUROPE



LG

The +

- *Excellent grip thanks to an oil-resistant sole.
- *Highest SR class anti-slip power, for perfect grip on all terrains. *Energy absorption in the heel area.
- *Improved fit and support

PURCHASE PACKAGING

| Ref. | Size | Carton |
|------------|------|--------|
| 9DWKT80036 | 36 | 6 |
| 9DWKT80037 | 37 | 6 |
| 9DWKT80038 | 38 | 6 |
| 9DWKT80039 | 39 | 6 |
| 9DWKT80040 | 40 | 6 |
| 9DWKT80041 | 41 | 6 |
| 9DWKT80042 | 42 | 6 |
| 9DWKT80043 | 43 | 6 |
| 9DWKT80044 | 44 | 6 |
| 9DWKT80045 | 45 | 6 |
| 9DWKT80046 | 46 | 6 |
| 9DWKT80047 | 47 | 5 |

Some sizes may only be available in certain countries

DESCRIPTION

The Work-it boot is a waterproof safety boot made from recycled PVC and lined with polyester. Non-slip on ceramic floors, its PVC sole is also antistatic and resistant to hydrocarbons. This work boot is equipped with a protective shell as well as a steel midsole against shocks and penetration.

SECTORS

Farming, silviculture and fishing

Light Industries

Regional/public authorities

Infrastructure, building industry

DIY

TECHNICAL FEATURES

| | |
|-------------------------|-------------|
| Color | Green |
| Color 2 | Black |
| Weight | 1096g |
| Upper | PVC |
| Toecap | Steel |
| Puncture resistant sole | Steel |
| Outsole | PVC nitrile |
| Lining | Polyester |

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)



EPI CAT. II

EN ISO 20345:2022

S5

Safety shoes

S5 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

SR

Resistance to slippage (ceramic floor + oil)

LG

Grip System - Unhooked heel