

Ref. **9FREH**

Multipurpose

High

High shoes



The +

- * Footbridge supplying torsional rigidity.
- * Padding for snug fit.

PURCHASE PACKAGING

Ref.	Size	Carton
9FREH36	36	10
9FREH37	37	10
9FREH38	38	10
9FREH39	39	10
9FREH40	40	10
9FREH41	41	10
9FREH42	42	10
9FREH43	43	10
9FREH44	44	10
9FREH45	45	10
9FREH46	46	10
9FREH47	47	10
9FREH48	48	10

Some sizes may only be available in certain countries

See also

DESCRIPTION

Upper in granulated leather, water repellent
 Padded collar for more protection and more comfort
 External sole in PU double density
 Antipenetration textile sole, nonmagnetic
 Composite toecap, nonmagnetic
 Breathable textile lining

SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Luggage handler,
 Delivery driver, ...

VARIANTS



9FREL

TECHNICAL FEATURES

Color	Black	Closing	Lacing closure
Upper	Full grain leather	Lining	Breathable 3D mesh
Toecap	Composite	Weight	602 g
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		
Main assembly	Injected		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/06/24/1221

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S3S

Safety shoes

S3S Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton+ closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value \geq 950 N) - Non-metallic insert, 3.0mm diameter puncture needle+ non-metallic insert type PS - resistance to penetration and water absorption of the upper- puncture resistance according to type- cleated outsole

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance