

Ref. **9GARH70**

Multipurpose

High

High shoes



The +

- \* Padded collar and bellows tongue for snug fit.
- \* Heel scuff cap.
- \* Shock absorbing EVA midsole.

### PURCHASE PACKAGING

Ref.	Size	Carton
9GARH70037	37	6
9GARH70038	38	6
9GARH70039	39	6
9GARH70040	40	6
9GARH70041	41	6
9GARH70042	42	6
9GARH70043	43	6
9GARH70044	44	6
9GARH70045	45	6
9GARH70046	46	6
9GARH70047	47	6

*Some sizes may only be available in certain countries*

### DESCRIPTION

GARNET is a leather safety shoe. The back of the model is equipped with a reinforcement to increase the protection and durability of the shoe. This model has a composite toe cap and a textile anti-perforation sole to make it a completely non-magnetic model. It is also equipped with a sole that is resistant up to 300°C on contact (for 1 minute).  
Note: GARNET 9GARH70 replaces the ALTAITE 9ALTH model.

### SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

## TECHNICAL FEATURES

Color	Brown	Insole	Removable, textile and foam
Color 2	Red	Main assembly	Cemented
Upper	Rectified leather and polyurethane coating	Closing	Lacing closure
Toecap	Composite	Weight	564 g
Puncture resistant sole	Textile	Lining	Breathable 3D mesh
Midsole	EVA		
Outsole	Rubber nitrile		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/02/22/0213

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)