

Ref. **9DUEN80**

Synthetic Boots

PU

Boots



### The +

- \* Flexible and lightweight for use all day long.
- \* Shaped cleats and raised heel for a perfect gripping
- \* Cold insulation.
- \* Antibacterial lining
- \* Scented comfort insole

### PURCHASE PACKAGING

Ref.	Size	Carton
9DUEN80036	36	5
9DUEN80037	37	5
9DUEN80038	38	5
9DUEN80039	39	5
9DUEN80040	40	5
9DUEN80041	41	5
9DUEN80042	42	5
9DUEN80043	43	5
9DUEN80044	44	5
9DUEN80045	45	5
9DUEN80046	46	5
9DUEN80047	47	5
9DUEN80048	48	5

*Some sizes may only be available in certain countries*

### DESCRIPTION

The DRY PU ENERGY model is a Polyurethane (PU) safety boot lined with an antibacterial lining.

This boot features a composite protective toe cap and textile midsole against impact and penetration.

Its PU outsole is reinforced with a TPU insert and insulates against the cold down to -20 ° C.

### SECTORS

Farming, silviculture and fishing

Energy (production and distribution)

Regional/public authorities

Infrastructure, building industry

## TECHNICAL FEATURES

Color	Green	Insole	Foam, removable and scented
Color 2	Black	Defined heel	
Weight	1 074 g		
Upper	Polyurethane		
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **CE 757776**

Delivered by BSI Group The Netherlands B.V (2797) Say Building- John M. Keynesplein 9- 1066 EP Amsterdam Netherlands



EPI CAT. II

EN ISO 20345:2011

S5

Safety shoes

**S5** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

CI

Shoe insulation against cold (30 minutes at -20°C)

FO

Hydrocarbons resistance