

Ref. **9FLU160**

Indoor and dry environments

Low

Low shoes



The +

- * Sporty design.
- * Lightweight.
- * Flexible.
- * Breathable.

PURCHASE PACKAGING

Ref.	Size	Carton
9FLU160038	38	10
9FLU160039	39	10
9FLU160040	40	10
9FLU160041	41	10
9FLU160042	42	10
9FLU160043	43	10
9FLU160044	44	10
9FLU160045	45	10
9FLU160046	46	10
9FLU160047	47	10

Some sizes may only be available in certain countries

DESCRIPTION

FLUORITE is a low safety shoe inspired by the running universe. Its upper made of polyester mesh and KPU (Thermoplastic polyurethane) provides great breathability and improved durability. The Polyester mesh lining offers comfort of use, just as its insole in textile and EVA with holes. The EVA/rubber outsole offers excellent cushioning, durability and grip. FLUORITE is metal free. It features a composite toe-cap and an anti-penetration plate made of textile which ensure both protection and flexibility. This shoe is ideal for work environments such as logistics, construction finishing works or DIY.

SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Painter,
Electrician,
Storekeeper, ...

TECHNICAL FEATURES

Color	Fluorescent green	Insole	Removable, perforated EVA
Color 2	Green	Main assembly	Cemented
Weight	498 g	Reinforcement material	KPU
Upper	Mesh	Reinforcement location	Upper
Toecap	Composite	Closing	Lacing closure
Puncture resistant sole	Textile	Lining	Breathable 3D mesh
Midsole	EVA	Defined heel	
Outsole	Rubber nitrile		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 2777/1373-01/E00-00

Delivered by SATRA Technology Europe Ltd (2777) Bracetown Business Park- Clonee- Dublin 15 Dublin Ireland



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)

COVERPERF - Breathability



Shoes tested in a certified laboratory (CTC) offering excellent breathability. Removal of perspiration above 4g/h.