

Ref. **9HYDR**

Outdoor

High

High shoes



### The +

- \*Heel and toe scuff caps for a longer shoe's lifespan.
- \*Padded collar and bellows tongue for snug fit.
- \*Defined heel for better safety especially on ladders.

### PURCHASE PACKAGING

Ref.	Size	Carton
9HYDR38	38	10
9HYDR39	39	10
9HYDR40	40	10
9HYDR41	41	10
9HYDR42	42	10
9HYDR43	43	10
9HYDR44	44	10
9HYDR45	45	10
9HYDR46	46	10
9HYDR47	47	10
9HYDR48	48	

*Some sizes may only be available in certain countries*

### DESCRIPTION

Composite toecap  
 Antipenetration textile sole  
 External sole in double density PU/Rubber  
 Upper in crazy horse leather  
 Lining: Waterproof and Thinsulate membrane  
 Reinforcement : front and back in TPU

### SECTORS

- Mining
- Extracting Oil and Gas
- Energy (production and distribution)
- Infrastructure, building industry

### APPLICATIONS

Builder,  
 Slater,  
 Ramp agent,  
 Luggage handler,  
 Site supervisor,  
 Docker, ...

## TECHNICAL FEATURES

Color	Black	Insole	Removable, textile and cushioned foam
Color 2	Red	Main assembly	Injected
Weight	778 g	Reinforcement material	Anti-abrasion Stark®
Upper	Full grain leather	Reinforcement location	Heel / Front
Toecap	Composite	Closing	Lacing closure
Puncture resistant sole	Textile	Lining	3M® Thinsulate® insulation
Midsole	PU		
Outsole	Rubber nitrile		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate ITASLNB21002888

Delivered by INTERTEK Italia S.p.A. (2575) Via Guido Miglioli 2/A 20063 Cernusco sul Naviglio - Milano (MI) Italy



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

WR

Water repellent shoe

HI

Shoe insulation against heat (30 minutes at 150°C)

HRO

Heat contact resistant outsole (60 seconds at 300°C)

CI

Shoe insulation against cold (30 minutes at -20°C)