

Ref. **9GAL130**

Indoor and dry environments

Low

Low shoes



The +

Lightweight (430 g in size 42)
Flexible and cushioning
Breathable

PURCHASE PACKAGING

Ref.	Size	Carton
9GAL130037	37	6
9GAL130038	38	6
9GAL130039	39	6
9GAL130040	40	6
9GAL130041	41	6
9GAL130042	42	6
9GAL130043	43	6
9GAL130044	44	6
9GAL130045	45	6
9GAL130046	46	6
9GAL130047	47	6

Some sizes may only be available in certain countries

See also

DESCRIPTION

The GALAXITE ESD HRO sneaker is very lightweight, flexible and breathable: at the forefront of comfort.

Its EVA/rubber outsole offers excellent cushioning, durability and grip.

GALAXITE is metal free. It features a composite toe-cap and an anti-penetration plate made of textile which ensure both protection and flexibility. This shoe is ideal for work environments such as logistics, construction finishing works or DIY.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

VARIANTS



9GAL120

TECHNICAL FEATURES

Color	Black	Insole	Removable, perforated EVA
Color 2	Red	Reinforce-ment material	TPU
Weight	430 g	Reinforce-ment location	Front
Upper	Mesh	Closing	Lacing closure
Toecap	Composite	Lining	Breathable 3D mesh
Puncture resistant sole	Textile		
Midsole	EVA		
Outsole	Rubber nitrile		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructi-ons

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructi-ons

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/05/21/0808

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

HRO

Heat contact resistant outsole (60 seconds at 300°C)

ESD

Electrostatic discharge shoe (EN 61340-5-1 standard)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

EN ISO 20345:2022

S1PS

Safety shoes

S1PS Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton + closed heel area- antistatic properties- energy-absorbing capacity of the heel + Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value \geq 950 N) - Non-metallic insert, 3.0mm diameter puncture needle

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance