

Ref. **9GAL140**

Indoor and dry environments

Low

Low shoes



The +

- *Trendy design.
- *Breathability.
- *PU2D injected sole.
- *Reflective stripes (9GAL500).

PURCHASE PACKAGING

Ref.	Size	Carton
9GAL140038	38	10
9GAL140039	39	10
9GAL140040	40	10
9GAL140041	41	10
9GAL140042	42	10
9GAL140043	43	10
9GAL140044	44	10
9GAL140045	45	10
9GAL140046	46	10
9GAL140047	47	10

Some sizes may only be available in certain countries

See also

VARIANTS



9GAL500

DESCRIPTION

GALENA is a low safety shoe inspired by sport. It features an upper made of perforated suede leather and a lining in Polyester mesh which provide high breathability. The outsole resists to fuel and oil contact. It is slip resistant on ceramic or steel floor and offer protection and stability to the wearer. Its PU/PU double density construction provides comfort and durability. The insole made of textile fabric and EVA with holes guarantees an efficient cushioning and breathability. This model is equipped with a steel toe-cap and anti-penetration plate. This shoe is ideal for working environments such as logistics, light industry or maintenance.

SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Painter,
Electrician,
Storekeeper, ...

TECHNICAL FEATURES

Color	Beige	Insole	Removable, perforated EVA
Color 2	Yellow	Main assembly	Injected
Weight	590 g	Closing	Lacing closure
Upper	Suede leather	Lining	Breathable 3D mesh
Toecap	Steel		
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/07/19/2029

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance