

Ref. **9FLH370**

Outdoor

High

High shoes



S3

SR

SC

FO



The +

- \*Shaped cleats: adherence and gripping on rough floors.
- \*Grooves for liquid and mud dispersement.
- \*Raised heel 1 cm and lateral edges: reinforced grip on ladders.
- \*Front TPU reinforcement.

### PURCHASE PACKAGING

Ref.	Size	Carton
9FLH370037	37	6
9FLH370038	38	6
9FLH370039	39	6
9FLH370040	40	6
9FLH370041	41	6
9FLH370042	42	6
9FLH370043	43	6
9FLH370044	44	6
9FLH370045	45	6
9FLH370046	46	6
9FLH370047	47	6
9FLH370048	48	6
9FLH370049	49	6

*Some sizes may only be available in certain countries*

See also

### VARIANTS



9FLL370

### DESCRIPTION

FLINT is a formidable efficiency safety shoe. Specially designed for construction industry, FLINT benefits from a PU / PU sole resistant to abrasion, oils and hydrocarbons and equipped with prominent grips. Its removable insole, made of textile and EVA with wide perforations, offers good evacuation of perspiration. FLINT features a toe-cap and an anti-penetration plate made of steel for optimal protection.

### SECTORS

Mining

Extracting Oil and Gas

Energy (production and distribution)

Infrastructure, building industry

## TECHNICAL FEATURES

Color	Caramel	Main assembly	Injected
Weight	701 g	Closing	Lacing closure
Upper	Action leather	Lining	Breathable 3D mesh
Toecap	Steel		
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	PU		
Insole	Removable, perforated EVA		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/04/21/0797

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2022

S3

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SR

Resistance to slippage (ceramic floor + oil)

SC

Abrasion resistance of the toe-caps

FO

Hydrocarbons resistance