# coverguard®

### TECHNICAL DATASHEET

## GALENA

9GAL140 Ref.

Indoor and dry environments

Low





#### **DESCRIPTION**

GALENA is a low safety shoe inspired by sport.

It features an upper made of perforated suede leather and a lining in Polyester mesh which provide high breathability.

The outsole resists to fuel and oil contact.

It is slip resistant on ceramic or steel floor and offer protection and stability to the wearer.

Its PU/PU double density construction provides comfort and durability. The insole made of textile fabric and EVA with holes guarantees an efficient cushioning and breathability.

This model is equipped with a steel toe-cap and anti-penetration plate. This shoe is ideal for working environments such as logistics, light industry or maintenance.

Painter,

Electrician,

Storekeeper, ...

**APPLICATIONS** 

#### **SECTORS**

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution







Low shoes

### The +

- \*Trendy design.
- \*Breathability.
- \*PU2D injected sole.
- \*Reflective stripes (9GAL500).

#### PURCHASE PACKAGING

Ref.	Size	Carton
9GAL140038	38	10
9GAL140039	39	10
9GAL140040	40	10
9GAL140041	41	10
9GAL140042	42	10
9GAL140043	43	10
9GAL140044	44	10
9GAL140045	45	10
9GAL140046	46	10
9GAL140047	47	10

Some sizes may only be available in certain countries

See also

#### **VARIANTS**



9GAL500



#### **TECHNICAL FEATURES**

ColorBeigeColor 2YellowWeight590 g

Upper Suede leather

Toecap Steel
Puncture resistant Steel

sole

Midsole PU
Outsole PU

Insole Removable, perforated EVA

Main assembly Injected

Closing Lacing closure
Lining Breathable 3D mesh

#### INSTRUCTION FOR USE AND STORAGE

#### Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

#### Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

#### Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

#### STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/07/19/2029

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France

C€ EPI CAT. II

**COVERPERF - Damping** 



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

EN ISO 20345:2022

SR

S1P

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

Resistance to slippage (ceramic floor + oil)

FO Hydrocarbons resistance

MAJ 06/02/2025