

Ref. **9GAL500**

Indoor and dry environments

Low

Low shoes



The +

- * Trendy design.
- * Breathability.
- * PU2D injected sole.
- * Reflective stripes.

PURCHASE PACKAGING

Ref.	Size	Carton
9GAL500038	38	10
9GAL500039	39	10
9GAL500040	40	10
9GAL500041	41	10
9GAL500042	42	10
9GAL500043	43	10
9GAL500044	44	10
9GAL500045	45	10
9GAL500046	46	10
9GAL500047	47	10

Some sizes may only be available in certain countries

See also

VARIANTS



9GAL140

DESCRIPTION

GALENA is a low safety shoe inspired by sport. It features an upper made of perforated suede leather and a lining in Polyester mesh which provide high breathability.

The sides retro-reflective strips improves wearer safety.

The outsole resists to fuel and oil contact. It is slip resistant on ceramic or steel floor and offer protection and stability to the wearer.

Its PU/PU double density construction provides comfort and durability.

The insole made of textile fabric and EVA with holes guarantees an efficient cushioning and breathability. This model is equipped with a steel toe-cap and anti-penetration plate. GALENA is ideal for working dry environments.

SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Painter,
Electrician,
Storekeeper, ...

TECHNICAL FEATURES

Color	Grey	Insole	Removable, perforated EVA
Color 2	Black	Main assembly	Injected
Weight	590 g	Closing	Lacing closure
Upper	Suede leather	Lining	Breathable 3D mesh
Toecap	Steel		
Puncture resistant sole	Steel		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/07/19/2029 EXT 01/07/19

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

COVERPERF - Damping



EN ISO 20345:2022

S1P

SR

FO

Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

Resistance to slippage (ceramic floor + oil)

Hydrocarbons resistance